SUBSEA SUPPORT VESSEL

Maersk Winner

The Maersk Supply Service flexible Subsea Support Vessels (SSV) are designed for a wide variety of work roles including subsea infrastructure deployment and recovery, inspection, maintenance and Repair (IMR) services and well intervention work scopes. Some of our vessels are also capable of mooring, anchor handling and/or general supply and cargo support for customers worldwide. These specialised vessels have highly skilled crews, optimal safety conditions and state-of-the-art equipment to help clients achieve their goals in a professional and cost-effective manner.



Key Features

- Dynamic position class 2
- 120 t full AHC crane
- 625 t anchor handling winch
- 245 t bollard pull
- 86 person accommodation
- Mezzanine deck for 2 WROVs



SUPPLY SERVICE

Classification

A1 Offshore Support Vessel (TOW, Supply) CRC ACCU

Dynamic positioning DP2

Reference systems 2 x DGPS Kongsberg

1 x HiPAP Simrad 1 x Fanbeam MDL

Motion reference units 3 x Gyrometer Raytheon

2 x Motion sensor Seatex 2 x Wind sensor STN Atlas

Deck Equipment

Crane Full AHC Capacity 120 t

120 t @1000 m 100t @ 2000 m

Anchor handling winch $1 \times 625 t$ Tow winches $2 \times 400 t$

Chain lockers 2 x 330 m³ + 2 x 230 m³

Shark jaws 2 x 700 t

Stern rollers 2 x 3.25 m x 4.00 m

Stern roller SWL 2 x 800 t

Towing pins 2 x S300 t Triplex

 $\begin{array}{ll} \text{Capstans} & 2 \times 15 \text{ t} \\ \text{Tugger winches} & 2 \times 15 \text{ t} \end{array}$

Moonpool 4.16 m x 3.34 m

FRC

Seabear 23MKII

Dimensions

Length (LOA) 90.3 m
Beam 23.0 m
Depth 9.5 m
Draft scantling 7.8 m
Deadweight 3842 t
Gross tonnage 6655

Deck capacities

 $\begin{array}{lll} \text{Deck load capacity} & 2500 \text{ t} \\ \\ \text{Deck strength} & \text{Aft 15 t/m}^2 \\ \\ \text{Fwd 10 t/m}^2 \\ \\ \text{Free deck area} & 770 \text{ m}^2 \\ \\ \text{Length} & 42.1 \text{ m} \\ \\ \text{Width} & 19.5 \text{ m} \\ \end{array}$

Propulsion / Bollard pull

Main engines 23480 BHP 4 x MAK 9M32C

Thrusters 2 x CP main propellers

1 x bow tunnel, 2040 BHP 1 x bow azimuth, 1770 BHP 2 x stern tunnel, 1200 BHP

Bollard pull 245,6 t

Accommodation

Person capacity 86

Tank capacities

 Base oil
 224 m³

 Brine
 364 m³

 Drill/ballast water
 2624 m³

 Fresh water
 760 m³

 Fuel
 2422 m³

 Oil based mud
 605 m³

*All figures and data believed to be correct, but not guaranteed

.....

Engage with us

w Maersksupplyservice.com

Facebook.com/MaerskSupplyService

in LinkedIn.com/company/Maersk-supply-service

www.instagram.com/maersksupplyservice

www.youtube.com/maersksupplyservice

Contact Information

For further information on vessel specifications, capacities or vessel availability, please do not hesitate to contact the Commercial Department at

chartering@maersksupplyservice.com or +45 73 73 73 73

